

T8 LED - g13

T8 LED TUBE 13W 3000K smd LED
900mm G13

Cod: **5455809**



G13
Lamp holder: G13



IP20
Protected from solid bodies larger
than 12 mm



F
Energy efficiency class F



II
Protection class II



CRI >80
Colour rendering index >80



Reer warranty
Reer guarantees the product for a
time duration of 3 years



Technical description

Product code: 5455809 | Category: LED tubes | Model: T8 LED - g13 | Product description: T8 LED TUBE 13W 3000K smd LED 900mm G13 | Warm-up time: < 1 | Ignition time: 0,5 | Color temperature (CCT): 3000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 1100 | Beam angle: 220° | Photobiological risk: RG0 (exempt) | LED Lifetime: 25.000 h | Maintenance factor: 70% | Number of switching cycles: > 12.500 | Energy efficiency class: F | Diameter (mm): 26 | Length (mm): 900 | Lamp holder: G13 | IP rating: IP 20 | Finishing colour: Opal White | Diffuser material: glass | Maximal working temperature: -20° C | Minimal working temperature: +40° C | Nominal power (W): 13 | Power factor: 0,9 | Power supply: 230V 50/60Hz | Insulation class: II | Dimmable: No | Quantity per package: 12 |

Lighting data

Color temperature (CCT)	3000K	Photobiological risk	RG0 (exempt)
MacAdam (SDCM)	< 6	LED Lifetime	25.000 h
MacAdam (SDCM)	< 1	Maintenance factor	70%
Ignition time	0,5	Number of switching cycles	> 12.500
Color render index (CRI)	> 80	Energy efficiency class	F
Lumen output (lm)	1100		
Beam angle	220°		

Mechanical data

Diameter (mm)	26	Finishing colour	Opal White
Length (mm)	900	Diffuser material	Glass
Lamp holder	G13	Maximal working temperature	-40° C
IP rating	IP 20	Minimal working temperature	-20° C

Electrical data

Insulation class	II	Quantity per package	12
Dimmable	No	Total quantity per boxing	12
Nominal power (W)	13		
Power factor	> 0,9		
Power supply	230V 50/60Hz		