

T8 LED nature - pink - g13

T8 LED TUBE 24W Pink SMD 1500mm
G13

Cod: **5455882**



G13
Lamp holder: G13



IP20
Protected from solid bodies larger
than 12 mm



Exempt
Product exempt from energy
labelling



II
Protection class II



CRI >85
Colour rendering index >85



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 5455882 | Category: LED tubes | Model: T8 LED nature - pink - g13 | Product description: T8 LED TUBE 24W Pink SMD 1500mm G13 | Warm-up time: < 1 | Ignition time: 1,0 | Color temperature (CCT): 3700K | Color render index (CRI): > 85 | MacAdam (SDCM): < 6 | Lumen output (lm): 2040 | Beam angle: 160° | Photobiological risk: RG0 (exempt) | LED Lifetime: 25.000 h | Maintenance factor: 70% | Number of switching cycles: > 12.500 | Energy efficiency class: Exempt | Diameter (mm): 26 | Length (mm): 1500 | Lamp holder: G13 | IP rating: IP 20 | Finishing colour: Rose | Diffuser material: glass | Maximal working temperature: -25° C | Minimal working temperature: +40° C | Nominal power (W): 24 | Power factor: 0,9 | Power supply: 230V 50/60Hz | Insulation class: II | Dimmable: No | Quantity per package: 10 |

Lighting data

MacAdam (SDCM)	< 1
Ignition time	1,0
Color temperature (CCT)	3700K
Color render index (CRI)	> 85
MacAdam (SDCM)	< 6
Lumen output (lm)	2040
Beam angle	160°

Photobiological risk	RG0 (exempt)
LED Lifetime	25.000 h
Maintenance factor	70%
Number of switching cycles	> 12.500
Energy efficiency class	Exempt

Mechanical data

Diameter (mm)	26
Length (mm)	1500
Lamp holder	G13
IP rating	IP 20

Finishing colour	Rose
Diffuser material	Glass
Maximal working temperature	-40° C
Minimal working temperature	-25° C

Electrical data

Nominal power (W)	24
Power factor	> 0,9
Power supply	230V 50/60Hz, 230V 50/60Hz
Insulation class	II
Dimmable	No

Quantity per package	10
Total quantity per boxing	25