



LED drop A80 opal E27

LED DROP BULB A80 HP E27 230V
24,5W 6500K

Cod: **5456024**



E27
Lamp holder: E27



IP20
Protected from solid bodies larger
than 12 mm



D
Energy efficiency class D



CRI >80
Colour rendering index >80



Reer warranty
Reer guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456024 | Category: LED lamps | Model: LED drop A80 opal E27 | Product description: LED DROP BULB A80 HP E27 230V 24,5W 6500K | Warm-up time: < 1 | Ignition time: 0,5 | Color temperature (CCT): 6500K | Color render index (CRI): > 80 | MacAdam (SDCM): < 5 | Lumen output (lm): 3452 | Beam angle: 200° | Photobiological risk: RG1 (low risk) | LED Lifetime: 15.000 h | Maintenance factor: 70% | Number of switching cycles: > 7.500 | Energy efficiency class: D | Diameter (mm): 80 | Height (mm): 155 | Lamp holder: E27 | IP rating: IP 20 | Finishing colour: Opal | Diffuser material: Technopolymer | Nominal power (W): 24,5 | Power factor: 0,5 | Power supply: 230V 50/60Hz | Dimmable: No | Quantity per package: 10 |

Lighting data

MacAdam (SDCM)	< 1	Photobiological risk	RG1 (low risk), RG1 (low risk)
Ignition time	0,5	LED Lifetime	15.000 h
Color temperature (CCT)	6500K	Maintenance factor	70%
Color render index (CRI)	> 80, > 80	Number of switching cycles	> 7.500
MacAdam (SDCM)	< 5, < 5	Energy efficiency class	D
Lumen output (lm)	3452		
Beam angle	200°		

Mechanical data

Diameter (mm)	80	IP rating	IP 20
Height (mm)	155	Finishing colour	Opal
Lamp holder	E27	Diffuser material	Technopolymer

Electrical data

Nominal power (W)	24,5	Quantity per package	1, 10
Power factor	> 0,5	Total quantity per boxing	20
Power supply	230V 50/60Hz, 230V 50/60Hz		
Dimmable	No		