

T8 LED aluminum - g13

T8 LED TUBE 10,3W 4000K SMD 909mm
G13

Cod: **5456029**



G13
Lamp holder: G13



IP20
Protected from solid bodies larger
than 12 mm



C
Energy efficiency class C



II
Protection class II



CRI >80
Colour rendering index >80



CAM compliant
CAM (Minimum Environmental
Criteria) compliant product for
indoor and outdoor installation



Reer warranty
Reer guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456029 | Category: LED tubes | Model: T8 LED aluminum - g13 | Product description: T8 LED TUBE 10,3W 4000K SMD 909mm G13 | Warm-up time: < 1 | Ignition time: 1,0 | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 1700 | Beam angle: 250° | Photobiological risk: RG0 (exempt) | LED Lifetime: 50.000 h | Maintenance factor: 70% | Number of switching cycles: > 25.000 | Energy efficiency class: C | Diameter (mm): 28 | Length (mm): 908 | Lamp holder: G13 | IP rating: IP 20 | Finishing colour: Opal White | Diffuser material: glass | Maximal working temperature: -20° C | Minimal working temperature: +45° C | Nominal power (W): 10 | Power factor: 0,9 | Power supply: 230V 50/60Hz | Insulation class: II | Dimmable: No | Quantity per package: 12 |

Lighting data

MacAdam (SDCM)	< 1
Ignition time	1,0
Color temperature (CCT)	4000K
Color render index (CRI)	> 80, > 80
MacAdam (SDCM)	< 6
Lumen output (lm)	1700
Beam angle	250°

Photobiological risk	RG0 (exempt)
LED Lifetime	50.000 h
Maintenance factor	70%
Number of switching cycles	> 25.000
Energy efficiency class	C

Mechanical data

Diameter (mm)	28
Length (mm)	908
Lamp holder	G13
IP rating	IP 20

Finishing colour	Opal White
Diffuser material	Glass
Maximal working temperature	+45° C
Minimal working temperature	-20° C

Electrical data

Nominal power (W)	10
Power factor	> 0,9
Power supply	230V 50/60Hz, 230V 50/60Hz
Insulation class	II
Dimmable	No

Quantity per package	12
Total quantity per boxing	12