



LED filament opal candle E14

LED FILAMENT OPAL CANDLE BULB
E14 6,2W 2700K 230V

Cod: **5456061**



E14
Lamp holder: E14



IP20
Protected from solid bodies larger
than 12 mm



E
Energy efficiency class E



CRI >80
Colour rendering index >80



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456061 | Category: LED lamps | Model: LED filament opal candle E14 | Product description: LED FILAMENT OPAL CANDLE BULB E14 6,2W 2700K 230V | Source type: LED | Type of filament: Parallel LED | Warm-up time: < 1 | Ignition time: 0,5 | Color temperature (CCT): 2700K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 806 | Beam angle: 320° | LED Lifetime: 15.000 h | Maintenance factor: 70% | Number of switching cycles: > 7.500 | Energy efficiency class: E | Diameter (mm): 35 | Height (mm): 98 | Lamp holder: E14 | IP rating: IP 20 | Finishing colour: Opal | Diffuser material: Glass | Nominal power (W): 6,2 | Power factor: 0,5 | Power supply: 230V 50/60Hz | Dimmable: No | Quantity per package: 10 |

Lighting data

Source type	LED	Beam angle	320°
Type of filament	Parallel LED	LED Lifetime	15.000 h
MacAdam (SDCM)	< 1	Maintenance factor	70%
Ignition time	0,5	Number of switching cycles	> 7.500
Color temperature (CCT)	2700K	Energy efficiency class	E
Color render index (CRI)	> 80, > 80		
MacAdam (SDCM)	< 6		
Lumen output (lm)	806		

Mechanical data

Diameter (mm)	35	IP rating	IP 20
Height (mm)	98	Finishing colour	Opal
Lamp holder	E14	Diffuser material	Glass

Electrical data

Nominal power (W)	6,2	Quantity per package	10
Power factor	> 0,5	Total quantity per boxing	100
Power supply	230V 50/60Hz, 230V 50/60Hz		
Dimmable	No		