



LED R50 - E14

LED BULB R50 230V E14 4W 4000K 110°
Erp

Cod: **5456153**



E14
Lamp holder: E14



IP20
Protected from solid bodies larger
than 12 mm



E
Energy efficiency class E



CRI >80
Colour rendering index >80



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456153 | Category: LED lamps | Model: LED R50 - E14 | Product description: LED BULB R50 230V E14 4W 4000K 110° Erp | Warm-up time: 1 | Ignition time: 0,5 | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 480 | Beam angle: 110° | LED Lifetime: 15.000 h | Maintenance factor: 70% | Number of switching cycles: > 7.500 | Energy efficiency class: E | Diameter (mm): 50 | Height (mm): 85 | Lamp holder: E14 | IP rating: IP 20 | Finishing colour: Opal | Diffuser material: Technopolymer | Nominal power (W): 4 | Power factor: 0,5 | Power supply: 230V 50/60Hz | Dimmable: No | Quantity per package: 10 |

Lighting data

MacAdam (SDCM)	< 1	LED Lifetime	15.000 h
Ignition time	0,5	Maintenance factor	70%
Color temperature (CCT)	4000K	Number of switching cycles	> 7.500
Color render index (CRI)	> 80, > 80	Energy efficiency class	E
MacAdam (SDCM)	< 6		
Lumen output (lm)	480		
Beam angle	110°		

Mechanical data

Diameter (mm)	50	IP rating	IP 20
Height (mm)	85	Finishing colour	Opal
Lamp holder	E14	Diffuser material	Technopolymer

Electrical data

Nominal power (W)	4	Quantity per package	10
Power factor	> 0,5	Total quantity per boxing	100
Power supply	230V 50/60Hz, 230V 50/60Hz		
Dimmable	No		