



LED globe G120 opal E27

GLOBE LED BULB G120 16W E27 5000K
Erp

Cod: **5456206**



E27
Lamp holder: E27



IP20
Protected from solid bodies larger
than 12 mm



E
Energy efficiency class E



CRI >80
Colour rendering index >80



Dimmable
Dimmable product



Reer warranty
Reer guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456206 | Category: LED lamps | Model: LED globe G120 opal E27 | Product description: GLOBO LED BULB G120 16W E27 5000K Erp | Warm-up time: 1 | Ignition time: 0,5 | Color temperature (CCT): 5000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 1901 | Beam angle: 220° | LED Lifetime: 15.000 h | Maintenance factor: 70% | Number of switching cycles: > 7.500 | Energy efficiency class: E | Diameter (mm): 60 | Height (mm): 110 | Lamp holder: E27 | IP rating: IP 20 | Finishing colour: Opal | Diffuser material: Technopolymer | Nominal power (W): 16 | Power factor: 0,5 | Power supply: 230V 50/60Hz | Dimmable: Yes | Quantity per package: 10 |

Lighting data

MacAdam (SDCM)	< 1
Ignition time	0,5
Color temperature (CCT)	5000K
Color render index (CRI)	> 80, > 80
MacAdam (SDCM)	< 6
Lumen output (lm)	1901
Beam angle	220°

LED Lifetime	15.000 h
Maintenance factor	70%
Number of switching cycles	> 7.500
Energy efficiency class	E

Mechanical data

Diameter (mm)	60
Height (mm)	110
Lamp holder	E27

IP rating	IP 20
Finishing colour	Opal
Diffuser material	Technopolymer

Electrical data

Nominal power (W)	16
Power factor	> 0,5
Power supply	230V 50/60Hz, 230V 50/60Hz
Dimmable	Yes

Quantity per package	10, 4
Total quantity per boxing	16