



LED globe G120 opal E27

GLOBE LED BULB G120 16W E27 6500K
Erp

Cod: **5456207**



E27
Lamp holder: E27



IP20
Protected from solid bodies larger
than 12 mm



E
Energy efficiency class E



CRI >80
Colour rendering index >80



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456207 | Category: LED lamps | Model: LED globe G120 opal E27 | Product description: GLOBO LED BULB G120 16W E27 6500K Erp | Warm-up time: 1 | Ignition time: 0,5 | Color temperature (CCT): 6500K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 1901 | Beam angle: 220° | LED Lifetime: 15.000 h | Maintenance factor: 70% | Number of switching cycles: > 7.500 | Energy efficiency class: E | Diameter (mm): 120 | Height (mm): 172 | Lamp holder: E27 | IP rating: IP 20 | Finishing colour: Opal | Diffuser material: Technopolymer | Nominal power (W): 16 | Power factor: 0,5 | Power supply: 230V 50/60Hz | Dimmable: No | Quantity per package: 10 |

Lighting data

MacAdam (SDCM)	< 1	LED Lifetime	15.000 h
Ignition time	0,5	Maintenance factor	70%
Color temperature (CCT)	6500K	Number of switching cycles	> 7.500
Color render index (CRI)	> 80, > 80	Energy efficiency class	E
MacAdam (SDCM)	< 6		
Lumen output (lm)	1901		
Beam angle	220°		

Mechanical data

Diameter (mm)	120	IP rating	IP 20
Height (mm)	172	Finishing colour	Opal
Lamp holder	E27	Diffuser material	Technopolymer

Electrical data

Nominal power (W)	16	Quantity per package	10, 4
Power factor	> 0,5	Total quantity per boxing	16
Power supply	230V 50/60Hz, 230V 50/60Hz		
Dimmable	No		