



# T8 LED alluminio - g13 - bi power - CCT

## TUBE T8 CCT 9W 600mm G13 (ERP)

Cod: **5456415**

G13  
Lamp holder: G13



IP20  
Protected from solid bodies larger  
than 12 mm



D  
Energy efficiency class D



II  
Protection class II



CRI >80  
Colour rendering index >80



ReeR warranty  
ReeR guarantees the product for a  
time duration of 3 years



### Technical description

Product code: 5456415 | Category: LED tubes | Model: LED tubes T8 aluminum | Product description: T8 TUBE CCT 9W 600mm G13 (ERP) | Warm-up time: < 1 | Ignition time: 1,0 | Color temperature (CCT): 3000 / 4000 / 6500K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Beam angle: 250° | BUG Rating: RG0 (exempt) | LED Lifetime: 30.000 h | Maintenance factor: 0,96 | Number of switching cycles: > 15.000 | Energy efficiency class: D | Width (mm): 28 | Length (mm): 604 | Lamp holder: G13 | IP rating: IP20 | Finishing colour: White Opal | Diffuser material: glass | Maximal working temperature: +45° C | Minimal working temperature: -15° C | Nominal power (W): 5 / 9 | Power supply: 230V 50/60Hz | Ballast: Integrated | Insulation class: II | Dimmable: No |

## Lighting data

|                          |                     |
|--------------------------|---------------------|
| MacAdam (SDCM)           | <1                  |
| Ignition time            | 1,0                 |
| Color temperature (CCT)  | 3000 / 4000 / 6500K |
| Color render index (CRI) | > 80, > 80          |
| MacAdam (SDCM)           | < 6                 |
| Beam angle               | 250°                |
| Photobiological risk     | RG0 (exempt)        |

|                            |          |
|----------------------------|----------|
| LED Lifetime               | 30.000 h |
| Maintenance factor         | 0,96     |
| Number of switching cycles | > 15.000 |
| Energy efficiency class    | D        |

## Mechanical data

|               |      |
|---------------|------|
| Diameter (mm) | 28   |
| Width (mm)    | 28   |
| Length (mm)   | 604  |
| Lamp holder   | G13  |
| IP rating     | IP20 |

|                             |            |
|-----------------------------|------------|
| Finishing colour            | White Opal |
| Diffuser material           | Glass      |
| Maximal working temperature | +45° C     |
| Minimal working temperature | -15° C     |

## Electrical data

|                   |                            |
|-------------------|----------------------------|
| Nominal power (W) | 5,9                        |
| Power supply      | 230V 50/60Hz, 230V 50/60Hz |
| Ballast           | Integrated, Integrated     |
| Insulation class  | II                         |
| Dimmable          | No                         |

|                           |    |
|---------------------------|----|
| Quantity per package      | 1  |
| Total quantity per boxing | 12 |