



T8 LED alluminio - g13 - bi power - CCT

TUBE T8 CCT 22W 1500mm G13 (ERP)

Cod: **5456417**

G13
Lamp holder: G13



IP20
Protected from solid bodies larger
than 12 mm



D
Energy efficiency class D



II
Protection class II



CRI >80
Colour rendering index >80



Reer warranty
Reer guarantees the product for a
time duration of 3 years



Technical description

Product code: 5456417 | Category: LED tubes | Model: LED tubes T8 aluminum | Product description: T8 TUBE CCT 22W 1500mm G13 (ERP) | Warm-up time: < 1 | Ignition time: 1,0 | Color temperature (CCT): 3000 / 4000 / 6500K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Beam angle: 200° | BUG Rating: RG0 (exempt) | LED Lifetime: 30.000 h | Maintenance factor: 0,96 | Number of switching cycles: > 15.000 | Energy efficiency class: D | Width (mm): 28 | Length (mm): 604 | Lamp holder: G13 | IP rating: IP20 | Finishing colour: White Opal | Diffuser material: glass | Maximal working temperature: +45° C | Minimal working temperature: -15° C | Nominal power (W): 12 / 22 | Power supply: 230V 50/60Hz | Ballast: Integrated | Insulation class: II | Dimmable: No |

Lighting data

MacAdam (SDCM)	< 1
Ignition time	1,0
Color temperature (CCT)	3000 / 4000 / 6500K
Color render index (CRI)	> 80, > 80
MacAdam (SDCM)	< 6
Beam angle	200°
Photobiological risk	RG0 (exempt)

LED Lifetime	30.000 h
Maintenance factor	0,96
Number of switching cycles	> 15.000
Energy efficiency class	D

Mechanical data

Diameter (mm)	28
Width (mm)	28
Length (mm)	604
Lamp holder	G13
IP rating	IP20

Finishing colour	White Opal
Diffuser material	Glass
Maximal working temperature	+45° C
Minimal working temperature	-15° C

Electrical data

Nominal power (W)	12 / 22
Power supply	230V 50/60Hz, 230V 50/60Hz
Ballast	Integrated, Integrated
Insulation class	II
Dimmable	No

Quantity per package	1
Total quantity per boxing	12