



LED globe G120 opal E27

GLOBE BULB G120 20W E27 6500K
OPAL (ERP)

Cod: **5456421**



E27
Lamp holder: E27



IP20
Protected from solid bodies larger
than 12 mm



E
Energy efficiency class E



CRI >80
Colour rendering index >80



CAM compliant
CAM (Minimum Environmental
Criteria) compliant product for
indoor and outdoor installation



Reer warranty
Reer guarantees the product for a
time duration of 3 years

Technical description

Product code: 5456421 | Category: LED lamps | Model: LED opal - E27 | Product description: GLOBE LAMP G120 20W E27 6500K OPAL (ERP) | Source type: LED | Type of filament: LED in parallel | Warm-up time: < 1 | Ignition time: 0,5 | Color temperature (CCT): 6500K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 2452 | Beam angle: 200° | LED Lifetime: 15.000h | Maintenance factor: 0,93 | Number of switching cycles: > 7.500 | Energy efficiency class: E | Width (mm): 120 | Height (mm): 172 | Lamp holder: E27 | IP rating: IP20 | Finishing colour: Opal | Diffuser material: Technopolymer | Nominal power (W): 20 | Power factor: > 0,7 | Power supply: 230V 50/60Hz | Dimmable: No | Quantity per package: 4 |

Lighting data

Source type	LED	Beam angle	200°
Type of filament	Parallel LED	LED Lifetime	15.000h
MacAdam (SDCM)	< 1	Maintenance factor	0,93
Ignition time	0,5	Number of switching cycles	> 7.500
Color temperature (CCT)	6500K	Energy efficiency class	E
Color render index (CRI)	> 80, > 80		
MacAdam (SDCM)	< 6		
Lumen output (lm)	2452		

Mechanical data

Width (mm)	120	IP rating	IP20
Height (mm)	172	Finishing colour	Opal
Lamp holder	E27	Diffuser material	Technopolymer

Electrical data

Nominal power (W)	20	Quantity per package	4
Power factor	0,7	Total quantity per boxing	16
Power supply	230V 50/60Hz, 230V 50/60Hz		
Dimmable	No		