DATA SHEET date: 31/10/2026

T8 LED - g13

Tubo T8 Led 15,5W 6500k 1200mm G13 Erp

Cod: **5456439**

G13
Lamp holder: G13

IP20
Protected from solid bodies larger than 12 mm

C
Energy efficiency class C

CRI >80
Colour rendering index >80

ReeR warranty
ReeR guarantees the product for a time duration of 3 years

RoHS Compliant

Technical description

T8 LED tube, with G13 socket and opal white diffuser. It uses an SMD LED source that guarantees uniform and stable light emission along the entire length of the tube, with low energy consumption.

ReeR Lighting Srl
Via Meucci 77, 10040 Leinì (TO) - Italia
Tel: +39 011 9969833 - Mail: vendite@reerlighting.com - www.reerlighting.com

Lighting data

MacAdam (SDCM)	< 1	Photobiological risk	RG0 (esente)
Ignition time	0.4	LED Lifetime	25.000 h
Color temperature (CCT)	6500K	Maintenance factor	95%
Color render index (CRI)	> 80	Number of switching cycles	> 12.500
MacAdam (SDCM)	< 6	Energy efficiency class	C
Lumen output (lm)	2500		
Beam angle	180°		

Mechanical data

Diameter (mm)	28	Finishing colour	Opal White
Length (mm)	1213	Diffuser material	Glass
Lamp holder	G13	Maximal working temperature	+45° C
IP rating	IP 20	Minimal working temperature	-20° C

Electrical data

Nominal power (W)	15,5	Quantity per package	25
Power factor	> 0,7	Total quantity per boxing	25
Power supply	230V 50/60Hz		
Dimmable	No		

ReeR Lighting Srl
Via Meucci 77, 10040 Leinì (TO) - Italia
Tel: +39 011 9969833 - Mail: vendite@reerlighting.com - www.reerlighting.com