LED panel 1200x600

PANEL LED 1200x600mm 48W 230V IP20 4000K

Cod: **6361019**

IP20
Protected from solid bodies larger than 12 mm

II
Protection class II

CRI >80
Colour rendering index >80

CAM compliant
CAM (Minimum Environmental Criteria) compliant product for indoor and outdoor installation

ReeR warranty
ReeR guarantees the product for a time duration of 3 years

Technical description

Product code: 6361019 | Category: Indoor luminaires | Model: LED panel 1200x600 | Product description: PANEL LED 1200x600mm 48W 230V IP20 4000K | Source type: SMD 4014 | Number of LEDs: 252 | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 4800 | Beam angle: 120° | LED Lifetime: 40.000 h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): F | Width (mm): 595 | Length (mm): 1195 | Height (mm): 10 | Weight (g): 5000 | IP rating: IP 20 | Finishing colour: White RAL9016 | Body material: Aluminum | Diffuser material: PS (polystyrene) | Maximal working temperature: -20° C | Minimal working temperature: +40° C | Nominal power (W): 48 | Power factor: > 0,9 | Power supply: 230V 50/60Hz | Ballast: Included | Insulation class: II | Dimmable: No |

Lighting data

|			
Source type	SMD 4014	Beam angle	120°, 120°
Number of LEDs	252	LED Lifetime	50.000 h
Color temperature (CCT)	4000K	Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): F
Color render index (CRI)	> 80, > 80		
MacAdam (SDCM)	< 6		
Lumen output (lm)	4800		

Mechanical data

|			
Width (mm)	595	Finishing colour	White RAL9016
Length (mm)	1195	Body material	Aluminum, Aluminum
Height (mm)	10	Diffuser material	PS (polystyrene)
Weight (g)	5000	Maximal working temperature	-40° C
IP rating	IP 20	Minimal working temperature	-20° C

Electrical data

Nominal power (W)	48	Dimmable	No
Power factor	> 0,9	Quantity per package	1
Power supply	230V 50/60Hz, 230V 50/60Hz	Total quantity per boxing	2
Ballast	Included, Included		
Insulation class	II		

Photometry

cd/klm
C0 - C180   C90 - C270
η = 100%

Technical drawing

295
1195

Accessories

Backlit and LED panel emergency kit

EMERGENCY KIT for LED PANEL

Cod: 6361127

Backlit and LED panel mounting kit

SUSPENSION MOUNTING KIT for PANEL code 6360746

Cod: 6360756

Backlit and LED panel mounting kit

BRACKET KIT FOR QUICK CEILING MOUNTING

Cod: 6360766

Backlit and LED panel mounting kit

CEILING MOUNTING KIT for 1200x600mm PANEL

Cod: 6361050

Reer Lighting is a brand of REER SPA
Via Carcano 32 - 10153 - Torino, Italy
Tel: +39 011 9969833 - Mail: vendite@reer.it - www.reerlighting.com