



Vela

VELA 8W IP54 3000K WHITE

Cod: **6361243**



IP54
Protected against dust and
splashes



I
Protection class I



CRI >80
Colour rendering index >80



CAM compliant
CAM (Minimum Environmental
Criteria) compliant product for
indoor and outdoor installation



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 6361243 | Category: Outdoor luminaires | Model: Appliques | Product description: VELA 8W IP54 3000K WHITE | Source type: SMD | Color temperature (CCT): 3000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 5 | Lumen output (lm): 745 | Beam angle: 120° | BUG Rating: Risk Group 1 (Low Risk) | LED Lifetime: L70 B50 50.000h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): E | Width (mm): 220 | Length (mm): 90 | Height (mm): 48 | Weight (g): 800 | IP rating: IP54 | IK rating: IK03 | Finishing colour: White RAL9003 | Body material: Aluminium | Diffuser material: Tempered glass | Maximal working temperature: +45° C | Minimal working temperature: -20° C | Nominal power (W): 8 | Power factor: > 0,8 | Power supply: 230V 50/60Hz | Ballast: Integrated | Insulation class: I | Dimmable: No |

Lighting data

Source type	SMD
Color temperature (CCT)	3000K
Color render index (CRI)	> 80
MacAdam (SDCM)	< 5
Lumen output (lm)	745
Beam angle	120°, 60°

Photobiological risk	Risk Group 1 (Low Risk), Risk Group 1 (Low Risk)
LED Lifetime	L70 B50 50.000h
Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): E, This contains a light source of energy efficiency class (EU2019/2015): E

Mechanical data

Width (mm)	220
Length (mm)	90
Height (mm)	48
Weight (g)	800
IP rating	IP54
IK rating	IK03


Finishing colour	White RAL9003, White RAL9003
Body material	Aluminium, Aluminum
Diffuser material	Tempered glass, Tempered glass
Maximal working temperature	+45° C
Minimal working temperature	-20° C

Electrical data

Nominal power (W)	8
Power factor	> 0,8
Power supply	230V 50/60Hz
Ballast	Integrated, Integrated
Insulation class	I

Dimmable	No
Quantity per package	1
Total quantity per boxing	20

Photometry



Technical drawing

