



Luna

LUNA 10W IP54 ANTHRACITE 4000K

Cod: **6361313**



IP54

Protected
splashes

against dust and



I

Protection class I



CRI >80

Colour rendering index >80



ReeR warranty

ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 6361313 | Category: Outdoor luminaires | Model: Appliques | Product description: LUNA 10W IP54 ANTHRACITE 4000K | Source type: SMD | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 3 | Lumen output (lm): 367 | Beam angle: 103° | BUG Rating: Risk Group 0 (exempt) | LED Lifetime: L70 B50 50.000h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): G | Width (mm): 176 | Length (mm): 97 | Height (mm): 36 | Weight (g): 450 | IP rating: IP54 | IK rating: IK08 | Finishing colour: Anthracite RAL7011 | Body material: Aluminium | Diffuser material: Polycarbonate | Maximal working temperature: +45° C | Minimal working temperature: -20° C | Nominal power (W): 10 | Power factor: > 0,5 | Power supply: 230V 50/60Hz | Ballast: Integrated | Insulation class: I | Dimmable: No |

Lighting data

Source type	SMD, SMD	Photobiological risk	Risk Group 0 (exempt)
Color temperature (CCT)	4000K	LED Lifetime	L70 B50 50.000h, L70 B50 50.000h
Color render index (CRI)	> 80, > 80	Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): G
MacAdam (SDCM)	< 3		
Lumen output (lm)	367		
Beam angle	103°		

Mechanical data

Width (mm)	176	Finishing colour	Anthracite RAL7011
Length (mm)	97	Body material	Aluminium, Aluminum
Height (mm)	36	Diffuser material	Polycarbonate
Weight (g)	450	Maximal working temperature	+45° C
IP rating	IP54, IP54	Minimal working temperature	-20° C
IK rating	IK08		

Electrical data

Nominal power (W)	10	Dimmable	No
Power factor	> 0,5	Quantity per package	1
Power supply	230V 50/60Hz, 230V 50/60Hz	Total quantity per boxing	20
Ballast	Integrated, Integrated		
Insulation class	I, I		

Technical drawing

