



Step Round

STEP ROUND 3W IP65 ANTHRACITE
4000K

Cod: **6361316**



IP65

Dustproof and protected against water jets



I

Protection class I



CRI >80

Colour rendering index >80



ReeR warranty

ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: 6361316 | Category: Outdoor luminaires | Model: Step Lights | Product description: STEP ROUND 3W IP65 ANTHRACITE 4000K | Source type: SMD | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 114 | Beam angle: 89° | BUG Rating: Risk Group 0 (exempt) | LED Lifetime: L70 B50 50.000h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): G | Height (mm): 30 | Weight (g): 240 | IP rating: IP 65 | IK rating: IK06 | Finishing colour: Anthracite RAL7011 | Body material: Aluminium | Diffuser material: Polycarbonate | Maximal working temperature: +45° C | Minimal working temperature: -20° C | Nominal power (W): 3 | Power factor: > 0,5 | Power supply: 230V 50/60Hz | Ballast: Integrated | Insulation class: I | Dimmable: No |

Lighting data

Source type	SMD, SMD
Color temperature (CCT)	4000K
Color render index (CRI)	> 80, > 80
MacAdam (SDCM)	< 6
Lumen output (lm)	114
Beam angle	89°

Photobiological risk	Risk Group 0 (exempt)
LED Lifetime	L70 B50 50.000h, L70 B50 50.000h
Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): G

Mechanical data

Height (mm)	30
Weight (g)	240
IP rating	IP 65
IK rating	IK06
Finishing colour	Anthracite RAL7011

Body material	Aluminium, Aluminum
Diffuser material	Polycarbonate
Maximal working temperature	+45° C
Minimal working temperature	-20° C

Electrical data

Nominal power (W)	3
Power factor	> 0,5
Power supply	230V 50/60Hz, 230V 50/60Hz
Ballast	Integrated, Integrated
Insulation class	I, I

Dimmable	No
Quantity per package	1
Total quantity per boxing	50

Technical drawing