



Step Square

STEP SQUARE 3W IP65 ANTHRACITE
4000K

Cod: **6361319**



IP65
Dustproof and protected against
water jets



I
Protection class I



CRI >80
Colour rendering index >80



ReeR warranty
ReeR guarantees the product for a
time duration of 3 years



Technical description

Product code: 6361319 | Category: Outdoor luminaires | Model: Step Lights | Product description: STEP SQUARE 3W IP65 ANTHRACITE 4000K | Source type: SMD | Color temperature (CCT): 4000K | Color render index (CRI): > 80 | MacAdam (SDCM): < 6 | Lumen output (lm): 158 | Beam angle: 89° | BUG Rating: Risk Group 0 (exempt) | LED Lifetime: L70 B50 50.000h | Energy efficiency class: This contains a light source of energy efficiency class (EU2019/2015): G | Width (mm): 110 | Length (mm): 110 | Height (mm): 30 | Weight (g): 270 | IP rating: IP 65 | IK rating: IK06 | Finishing colour: Anthracite RAL7011 | Body material: Aluminium | Diffuser material: Tempered glass | Maximal working temperature: +45° C | Minimal working temperature: -20° C | Nominal power (W): 3 | Power factor: > 0,5 | Power supply: 230V 50/60Hz | Ballast: Integrated | Insulation class: I | Dimmable: No |

Lighting data

Source type	SMD, SMD
Color temperature (CCT)	4000K
Color render index (CRI)	> 80, > 80
MacAdam (SDCM)	< 6
Lumen output (lm)	158
Beam angle	89°

Photobiological risk	Risk Group 0 (exempt)
LED Lifetime	L70 B50 50.000h, L70 B50 50.000h
Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): G

Mechanical data

Width (mm)	110
Length (mm)	110
Height (mm)	30
Weight (g)	270
IP rating	IP 65
IK rating	IK06

Finishing colour	Anthracite RAL7011
Body material	Aluminium, Aluminum
Diffuser material	Tempered glass, Tempered glass
Maximal working temperature	+45° C
Minimal working temperature	-20° C

Electrical data

Nominal power (W)	3
Power factor	> 0,5
Power supply	230V 50/60Hz, 230V 50/60Hz
Ballast	Integrated, Integrated
Insulation class	I, I

Dimmable	No
Quantity per package	1
Total quantity per boxing	50

Technical drawing

