



Vela Mini

Vela Mini 1x6Watt IP54 4000k Corten

Cod: **6361344**



IP54 Protected against dust and splashes



I Protection class I



CRI >80 Colour rendering index >80



CAM compliant
CAM (Minimum Environmental Criteria) compliant product for indoor and outdoor installation



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Compact LED wall light for interior and exterior walls, with a clean design. Available in a standard or mini version for more discreet installations. Ideal for entrances, hallways, terraces, and modern facades.

Lighting data

Source type	SMD	Photobiological risk	Risk Group 1 (Low Risk)
Color temperature (CCT)	4000K	LED Lifetime	L70 B50 50.000h
Color render index (CRI)	> 80	Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): E
MacAdam (SDCM)	< 5		
Lumen output (lm)	592		
Beam angle	60°		


Mechanical data

Width (mm)	170	Finishing colour	Corten
Length (mm)	80	Type of finishing	Polyester powder coated
Height (mm)	40	Body material	Aluminium
Weight (g)	500	Diffuser material	Tempered glass
IP rating	IP 54	Maximal working temperature	+45° C
IK rating	IK 03	Minimal working temperature	-20° C

Electrical data

Nominal power (W)	6	Dimmable	No
Power factor	> 0,8	Quantity per package	1
Power supply	230V 50/60Hz	Total quantity per boxing	20
Ballast	Integrated		
Insulation class	I		

Photometry



Technical drawing

