



Gamma 2 CCT 12W

GAMMA2 Wall Light 2X6W CCT Corten

Cod: **6361417**



IP65

Dustproof and protected against water jets



I

Protection class I



CRI >80

Colour rendering index >80



Variable CCT

Selectable colour temperature



ReeR warranty

ReeR guarantees the product for a time duration of 3 years



Technical description

Dual-beam wall sconce with CCT technology for wider, more defined light beams. A reliable and versatile solution for perimeter lighting of buildings, porches, and outdoor walkways.

Lighting data

Source type	SMD	Beam angle	70°
MacAdam (SDCM)	< 1	Photobiological risk	Risk Group 1 (Low Risk), Risk Group 1 (Low Risk)
Ignition time	0.4	LED Lifetime	L70 B50 50.000h
Color temperature (CCT)	3000 / 3500 / 4000K	Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): E
Color render index (CRI)	> 80		
MacAdam (SDCM)	< 5		
Lumen output (lm)	902 / 1002 / 690		


Mechanical data

Width (mm)	55	Finishing colour	Corten 8011
Length (mm)	145	Body material	Aluminum, Aluminum
Height (mm)	110	Diffuser material	Tempered glass
Weight (g)	727	Maximal working temperature	+40° C
IP rating	IP 65	Minimal working temperature	-15° C
IK rating	IK 06		

Electrical data

Nominal power (W)	12	Dimmable	No
Power factor	> 0,8	Quantity per package	1
Power supply	230V 50/60Hz	Total quantity per boxing	20
Ballast	Integrated		
Insulation class	I		

Photometry



Technical drawing

