



# Teatro round 8,5W

TEATRO ROUND 8,5W 4000K 15°  
chrome frame

Cod: **MIC0216**



IP20  
Protected from solid bodies larger  
than 12 mm



II  
Protection class II



CRI >90  
Colour rendering index >90



CAM compliant  
CAM (Minimum Environmental  
Criteria) compliant product for  
indoor and outdoor installation



ReeR warranty  
ReeR guarantees the product for a  
time duration of 3 years



## Technical description

Product code: MIC0216 | Category: Indoor luminaires | Model: Teatro round 8,5W | Product description: TEATRO ROUND 8,5W 4000K 15° chrome frame | Source type: COB | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 648 | Beam angle: 15° | Photobiological risk: RG2 (moderate risk) | LED Lifetime: 50.000 h | Diameter (mm): 68 | Height (mm): 80 | Recess hole (mm): Ø 60 | Weight (g): 190 | IP rating: IP 20 | Finishing colour: White RAL9003 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: PC (polycarbonate) | Maximal working temperature: -25° C | Minimal working temperature: +50° C | Nominal power (W): 8,5 | Power factor: > 0,5 | Power supply: 220/240V 50/60Hz | Ballast: Included | Insulation class: II | Dimmable: No |

## Lighting data

|                          |            |                      |                     |
|--------------------------|------------|----------------------|---------------------|
| Source type              | COB, COB   | Beam angle           | 15°                 |
| Color temperature (CCT)  | 4000K      | Photobiological risk | RG2 (moderate risk) |
| Color render index (CRI) | > 90, > 90 | LED Lifetime         | 50.000 h            |
| MacAdam (SDCM)           | < 3, < 3   |                      |                     |
| Lumen output (lm)        | 648        |                      |                     |

## Mechanical data

|                  |        |                                |                                                     |
|------------------|--------|--------------------------------|-----------------------------------------------------|
| Diameter (mm)    | 68     | Type of finishing              | Polyester powder coated,<br>Polyester powder coated |
| Height (mm)      | 80, 80 | Body material                  | Aluminum, Aluminum                                  |
| Recess hole (mm) | Ø 60   | Diffuser material              | PC (polycarbonate)                                  |
| Weight (g)       | 190    | Maximal working<br>temperature | +50° C                                              |
| IP rating        | IP 20  | Minimal working temperature    | -25° C                                              |
| Finishing colour | Nickel |                                |                                                     |

## Electrical data

|                   |                    |                      |    |
|-------------------|--------------------|----------------------|----|
| Nominal power (W) | 8,5                | Dimmable             | No |
| Power factor      | > 0,5              | Quantity per package | 1  |
| Power supply      | 220/240V 50/60Hz   |                      |    |
| Ballast           | Included, Included |                      |    |
| Insulation class  | II                 |                      |    |

## Photometry



## Technical drawing

