



Effetto 28W

EFFETTO 4000K 28W 60° Black (700mA)

Cod: **MTK0032**



IP20
Protected from solid bodies larger than 12 mm



II
Protection class II



CRI >90
Colour rendering index >90



CAM compliant
CAM (Minimum Environmental Criteria) compliant product for indoor and outdoor installation



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Professional LED track light designed for high-performance accent and general lighting. Available with various optics for narrow or diffuse beams, ideal for shaping light in spaces. A solution suitable for retail, showrooms, hospitality, and commercial environments, with constant current power supply.

Lighting data

Color temperature (CCT)	4000K	Photobiological risk	RG1 (low risk), RG1 (low risk)
Color render index (CRI)	> 90, > 90	LED Lifetime	50.000 h
MacAdam (SDCM)	< 3, < 3		
Lumen output (lm)	2852		
Beam angle	60°, 60°		


Mechanical data

Diameter (mm)	95	Type of finishing	Polyester powder coated, Polyester powder coated
Height (mm)	113	Body material	Aluminum, Aluminum
Weight (g)	1200	Diffuser material	Tempered glass
IP rating	IP 20	Maximal working temperature	+55° C
Finishing colour	Black RAL9004	Minimal working temperature	-20° C

Electrical data

Nominal power (W)	28	Dimmable	No
Power factor	> 0,9	Quantity per package	1
Power supply	220/240V 50/60Hz	Total quantity per boxing	10
Ballast	Integrated, Integrated		
Insulation class	II		

Photometry



Technical drawing

