



Risalto 32W

RISALTO 4000K 32W 40° Black (850mA)

Cod: **MTK0071**



IP20
Protected from solid bodies larger than 12 mm



I
Protection class I



CRI >90
Colour rendering index >90



CAM compliant
CAM (Minimum Environmental Criteria) compliant product for indoor and outdoor installation



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Product code: MTK0071 | Category: Indoor luminaires | Model: Risalto 32W | Product description: RISALTO 4000K 32W 40° Black (850mA) | Color temperature (CCT): 4000K | Color render index (CRI): > 90 | MacAdam (SDCM): < 3 | Lumen output (lm): 3210 | Beam angle: 40° | Photobiological risk: RG1 (low risk) | LED Lifetime: 50.000 h | Diameter (mm): 95 | Height (mm): 113 | Weight (g): 1200 | IP rating: IP 20 | Finishing colour: Black RAL9004 | Type of finishing: Polyester powder coated | Body material: Aluminum | Diffuser material: Tempered glass | Maximal working temperature: -20° C | Minimal working temperature: +55° C | Nominal power (W): 32 | Power factor: > 0,9 | Power supply: 220/240V 50/60Hz | Ballast: Integrated | Insulation class: I | Dimmable: No |

Lighting data

Color temperature (CCT)	4000K
Color render index (CRI)	> 90
MacAdam (SDCM)	< 3
Lumen output (lm)	3210
Beam angle	40°

Photobiological risk	RG1 (low risk), RG1 (low risk)
LED Lifetime	50.000 h

Mechanical data

Diameter (mm)	95
Height (mm)	113
Weight (g)	1200
IP rating	IP 20
Finishing colour	Black RAL9004


Type of finishing	Polyester powder coated, Polyester powder coated
Body material	Aluminum, Aluminum
Diffuser material	Tempered glass
Maximal working temperature	+55° C
Minimal working temperature	-20° C

Electrical data

Nominal power (W)	32
Power factor	> 0,9
Power supply	220/240V 50/60Hz
Ballast	Integrated, Integrated
Insulation class	I

Dimmable	No
Quantity per package	1
Total quantity per boxing	10

Photometry



Technical drawing

