



Focus 20W

Floodlight FOCUS 20W 3000K 24° White

Cod: **MTK0145**



IP20
Protected from solid bodies larger than 12 mm



I
Protection class I



CRI >90
Colour rendering index >90



CAM compliant
CAM (Minimum Environmental Criteria) compliant product for indoor and outdoor installation



ReeR warranty
ReeR guarantees the product for a time duration of 3 years



Technical description

Compact LED track spotlight designed for precise and controlled accent lighting. Different wattages and beam angles allow you to adapt the light to specific spaces and surfaces. Ideal for retail, showrooms, hospitality, and modern commercial environments.

Lighting data

Source type	COB	Beam angle	24°
MacAdam (SDCM)	< 1	Photobiological risk	Risk Group 1 (Low Risk)
Ignition time	0.4	LED Lifetime	L70 B50 50.000h
Color temperature (CCT)	3000K	Energy efficiency class	This contains a light source of energy efficiency class (EU2019/2015): G
Color render index (CRI)	> 90		
MacAdam (SDCM)	< 4		
Lumen output (lm)	2100		


Mechanical data

Diameter (mm)	65	Finishing colour	White RAL9010
Height (mm)	198	Body material	Aluminum
Weight (g)	400	Diffuser material	Polycarbonate
IP rating	IP 20	Maximal working temperature	+55° C
IK rating	IK 08	Minimal working temperature	-20° C

Electrical data

Nominal power (W)	20	Dimmable	No
Power factor	> 0,5	Quantity per package	1
Power supply	230V 50/60Hz	Total quantity per boxing	10
Ballast	Integrated		
Insulation class	I		

Photometry



Technical drawing

